

J275 F

Fixed traffic bollard



Type of operator

Fixed

Height

600 or 800 mm



- Power supply and wiring not required
- Easy installation and limited excavation depth.
- Guarantees aesthetic coherency in multiple installations together with retractable bollards.




DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	J275 F H600	J275 F H800	J275 F H600 Stainless steel	J275 F H800 Stainless steel
Cylinder height from ground	600 mm	800 mm	600 mm	800 mm
Cylinder diameter	275 mm			
Cylinder treatment	Cataphoresis and polyester powder paint, dark grey metallised RAL 7021			Satin finish
Reflective strip height	55 mm			
Standard reflecting strip colour	Orange			
Break in resistance	128.000 J			207.000 J
Total weight	34 Kg	38 Kg	34 Kg	38 Kg

PAINTED STEEL FAMILY MODELS

Model	Item code
J275 F H600	116020
J275 F H800	116021

For custom paint finishes, please contact the local sales representative.



PACKS

- J275 F is equipped with:**
- steel cylinder with cataphoresis treatment and metallised dark grey powder coated painting
 - flashing LED lights ring*

INOX AISI 316L FAMILY MODELS

Model	Item code
J275 F H600 Stainless steel	116040
J275 F H800 Stainless steel	116041

PACKS

- J275 F INOX is equipped with:**
- AISI 316L satin-finished stainless steel cylinder
 - flashing LED lights ring*

INSTALLATION ACCESSORIES



Fixed bollard fixing frame JPF275

116120

OPTIONAL ACCESSORIES



Pit cover JC275

116201

NOTE

(*) The power supply unit (24 V) and the cable (2x1.5 mm) for the flashing light are not supplied.