

J275 SA

Retractable traffic bollard



Type of operator

Semiautomatic

Height

600 mm



- Power supply and wiring not required
- Kept lock in low position (against accidental release).
- Simple and safe movements thanks to the dedicated release key



DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	J275 SA H600	J275 SA H600 Stainless steel
Type of operator	Single-acting gas operator	
Cylinder height from ground	600 mm	
Cylinder diameter	275 mm	
Cylinder treatment	Cataphoresis and polyester powder paint, dark grey metallised RAL 7021	Satin finish
Reflective strip height	55 mm	
Standard reflecting strip colour	Orange	
Release device	Key operated (supplied)	
Impact resistance	38.000 J	67.000 J
Break in resistance	128.000 J	207.000 J
Pit weight	55 Kg	
Traffic bollard weight	70 Kg	
Load class (EN 124)	C250 (25t)	

PAINTED STEEL FAMILY MODELS

Model	Item code
J275 SA H600	116050

For custom paint finishes, please contact the local sales representative.



PACKS

- J275 SA is equipped with:**
- steel cylinder with cataphoresis treatment and metallised dark grey powder coated painting
 - flashing LED lights ring*
 - mechanical lock in raised position with special release key (No. 2 release keys provided)

INOX AISI 316L FAMILY MODELS

Model	Item code
J275 SA H600 Stainless steel	116060

PACKS

- J275 SA INOX is equipped with:**
- AISI 316L satin-finished stainless steel cylinder
 - flashing LED lights ring*
 - mechanical lock in raised position with special release key (No. 2 release keys provided)

INSTALLATION ACCESSORIES



Pit JP275/600 complete with counter frame for bollard H600

1161001

OPTIONAL ACCESSORIES



Release keys kit (5 keys)

390084



Pit cover JC275

116201

NOTE

(*) The power supply unit (24 V) and the cable (2x1.5 mm) for the flashing light are not supplied.